

Rating	
16A 125V AC	1/3HP 125V AC
10A 250V AC	1/2HP 250V AC
Contact resistance	
50mΩ Max	
Insulation resistance	
DC 500V 100MΩ Min	
Dielectric strength	
AC 1500V 1 minute	
Cut-out	

FEATURES


- * MATERIAL: Frame is nylon (UL flame: 94V-2). Terminals are silver plated brass.
- * Illuminated actuators are molded in PC, available with red, amber, green, blue and white colors.
- * Snap-in mounting, easy to install switch into panel.
- * Waterproof cover is optional.
- * The only difference between R13-66B and R13-66B6 is the rocker style.



	X	
	Y	
Actuator	X	Y
0.75-1.25	18.0±1	13.0±1
1.25-2	18.4±1	13.0±1
2-3	18.8±1	13.0±1

Cut-out for X8 ROCKER

	X	
	Y	
Actuator	X	Y
0.75-1.25	18.4±1	13.0±1
1.5-2.5	18.8±1	13.0±1



Ordering number instruction


R13-66 - [] - []

FUNCTION

Different button (按鈕不同)



Illuminated / Different button (帶燈/按鈕不同)




Momentary / Illuminated / Different button (彈回/帶燈/按鈕不同)



Different position / Different button (動作特性不同/按鈕不同)



Momentary / Different button (彈回/按鈕不同)



Independent circuit / Different button (獨立通路/按鈕不同)



Waterproof (防水)



TERMINAL

0 2	187° SQ
0 5	SO
0 9	PC
1 0	PC ANGLE
1 2	SO

ROCKER

A/B/BF/C/D/E/F	G/H/I
B, BF transparent	
A5	B, BF transparent
B2/B2F	
L/B4/BF4	
AP/CP/DP/HP/IP	
B6/B6F	
B6, B6F transparent	
A8/B8/B8F/C8	
F8	