



MODEL NO.	SWITCH POSITION		
	ON	NONE	ON
4P-1			
Term. Comm	2-3,5-6 8-9,11-12	OPEN	2-1,5-4 8-7,11-10

**SPECIFICATIONS:**

- 1.MOVABLE CONTACT: Copper alloy, silver plated
- 2.TERMINALS: Copper alloy, silver plated
- 3.RATING: 5Amps with resistive load @ 125VAC or 28VDC  
2Amps with resistive load @ 250VAC
- 4.CONTACT RESISTANCE: 10m-ohms max. initial
- 5.INSULATION RESISTANCE: 1,000M-ohms min.
- 6.DIELECTRIC STRENGTH: 1,500V RMS @ sea level
- 7.ELECTRICAL LIFE: 50,000 make and break cycles at full load
- 8.OPERATING TEMPERATURE: -30°C to +85°C

Rev.	Date	Description	Remark
YUBRIGHT		YUBRIGHT CO., LTD.	
Title		TOGGLE SWITCH	
Date		20130208	
File		SWT030	
P/N		SA-RU0030.1204	
Dwg. No.		SARU0030120401	
Rev.		A	
RoHS		✓	
App.		b37	
Unless otherwise specified, demensions are in millimeters.		File	