

# Technical specifications


## Alkaline

Pro Power



LR03

Panasonic Typical Dimensions



IEC Dimensions (mm)		
Dimension	Maximum	Minimum
A	44,5	
B		43,3
C		4,3
E	0,5	
F	3,8	
G		0,8
Ø	10,5	9,5

## Specifications

<b>Name</b>	LR03 / S / AAA / AM4 / MICRO / MN2400 / 24A / 24AC
<b>Made in</b>	Belgium
<b>Type</b>	Alkaline Foil
<b>Nominal Voltage</b>	1,5 Volt
<b>Electrolyte</b>	Potassium Hydroxide
<b>Average weight</b>	11,2 g
<b>Storage temp. range</b>	+10°C ~ +25°C
<b>Operating temp. range</b>	-20°C ~ +45°C
<b>Average Impedance</b>	+/- 135 m-Ohm @ 1kHz fresh
<b>Heavy metals</b>	No added mercury (Hg), Cadmium (Cd) or Lead (Pb)
<b>Compliant to</b>	IEC 60086 non dangerous goods regulation Nordic ecolabeling (white Swan) EU directive 2006/66/EC
<b>Recommended cut off voltage</b>	0,8V per cell






For more information:

[www.panasonic-batteries.com](http://www.panasonic-batteries.com)

**Panasonic**  
ideas for life

## Typical discharge values

LR03



Copyright© Panasonic Energy Europe N.V. ("PECE") 2010 - All rights reserved. The information contained herein is believed to be correct. However no warranty is made, either expressed or implied regarding the accuracy or the results to be obtained from the use of such information. Test results are strictly according to IEC conditions. Capacities of batteries are depending on drain, temperature and cut-off voltage. Data are subject to change. 07/2010.

Promoter: Panasonic Energy Europe N.V., P. Celis, Brusselsesteenweg 502, 1731 Zellik, Belgium

For more information: [www.panasonic-batteries.com](http://www.panasonic-batteries.com)