


Батареи литиевые (батареи литий-тионил хлорид Li-SOCl₂)



Li-SOCl ₂ (Energy Type)										
Model		Nominal Voltage (V)	Dimensions φ xH (mm)	Discharge Characteristics(23°C)				Cut-off Voltage (V)	Weight Approx (g)	Operating Temperature (°C)
GB	IEC			Nominal Capacity (mAh)	Standard Current (mA)	Max Discharge Current				
							Continuous (mA)	Pulse (mA)		
ER10280		3.6	10.0×28.0	450	0.5	10.0	20.0	2.0	5.0	-55~+85
ER10450	AAA	3.6	10.0×45.0	800	1.0	10.0	20.0	2.0	9.0	-55~+85
ER13150		3.6	13.0×15.0	450	0.5	10.0	20.0	2.0	5.5	-55~+85
ER14250	1/2AA	3.6	14.5×25.0	1200	0.5	50.0	100.0	2.0	10.0	-55~+85
ER14335	2/3AA	3.6	14.5×33.5	1650	0.7	50.0	100.0	2.0	13.0	-55~+85
ER14505	AA	3.6	14.5×50.5	2400	1.0	100.0	200.0	2.0	19.0	-55~+85
ER17335		3.6	17.5×33.5	2100	1.0	100.0	200.0	2.0	15.0	-55~+85
ER17505		3.6	17.5×50.5	3400	1.0	100.0	200.0	2.0	29.0	-55~+85
ER18505	A	3.6	18.5×50.5	3500	1.0	100.0	200.0	2.0	32.0	-55~+85
ER26500	C	3.6	26.2×50.5	9000	2.0	200.0	400.0	2.0	55.0	-55~+85
ER34615	D	3.6	34.2×61.5	19000	3.0	200.0	400.0	2.0	107.0	-55~+85
9V Li		10.8	17.8×27.5	1200	50	100			40	-55~+85

Li-SOCI2(Power Type)



Model		Nominal Voltage (V)	Dimensions Diameter*Height (MM)	Discharge Characteristics(23°C)				Cut-off Voltage (V)	Weight Approx (g)	Operating Temperature (°C)
GB	IEC			Nominal Capacity (mAh)	Standard Current (mA)	Max Discharge Current				
						Continuous (mA)	Pulse (mA)			
ER14250M	1/2AA	3.6	14.4×25.0	750	0.5	100.0	300	2.0	10	-55→+85
ER14335M	2/3AA	3.6	14.5×29.0	1200	0.7	200.0	400	2.0	13	-55→+85
ER14505M	AA	3.6	14.5×50.5	1800	1.0	400.0	800	2.0	19	-55→+85
ER17335M		3.6	17.0×33.5	1700	1.0	500.0	1000	2.0	20	-55→+85
ER17505M		3.6	17.5×50.5	2800	1.0	500.0	1000	2.0	29	-55→+85
ER18505M	A	3.6	18.5×50.5	3000	1.0	600.0	1000	2.0	32	-55→+85
ER26500M	C	3.6	26.2×50.5	6500	2.0	1000.0	1500	2.0	55	-55→+85
ER34615M	D	3.6	34.2×61.5	16500	10.0	2000.0	3000	2.0	106	-55→+85

Li-SOCI2(High Temperature Type)



Model		Nominal Voltage (V)	Dimensions Diameter*Height (MM)	Discharge Characteristics(23°C)				Cut-off Voltage (V)	Weight Approx (g)	Operating Temperature (°C)
GB	IEC			Nominal Capacity (mAh)	Standard Current (mA)	Max Discharge Current				
						Continuous (mA)	Pulse (mA)			
ER14250S	1/2AA	3.6	14.5×25.0	550	0.05	50.0	100	2.0	10	-40→+150
ER14505S	AA	3.6	14.5×50.5	1600	0.1	100.0	200	2.0	19	-40→+150
ER18505S	A	3.6	18.5×50.5	3200	1.0	200.0	300	2.0	32	-40→+150
ER26500S	C	3.6	26.2×50.0	4100	0.1	100.0	200	2.0	55	-40→+150
ER34615S	D	3.6	34.2×61.5	10500	0.1	200.0	300	2.0	107	-40→+150