



SPECIFICATION

1. Rated Voltage 1.5 V
2. Operating Voltage 1~2V
3. Max. Rated Current 10mA
4. Coil Resistance $50 \pm 7.5 \Omega$
5. Coil Impedance 140Ω
6. Min. Sound Pressure Level 80dB/10cm
7. Resonant Frequency 2048Hz
8. Case Material/Color Noryl/Black
9. Operating Temperature $-20 \sim +70^\circ\text{C}$
10. Store Temperature $-30 \sim +80^\circ\text{C}$
11. Weight 2g

Compliance with RoHS

KEPO NINGBO KEPO ELECTRONIC CO.,LTD
<http://www.chinaacoustic.com>

Magnetic Transducer QUARTZ-1
 KP12-G185C-2933

No.	DESCRIPTION	MENDER	DATE	UNIT	SCALE
TOLERANCES UNLESS NOTED OTHERWISE				DWG/NO.	
XX ±	APPROVALS	LHJ	08.07.07	OEM2933R	
XXX ±	DRAWN			SHR	VER 1.0
90° ANGLES -1°	CHECKED				
FIRST ANGLE PROJECTION	APPROVED				

KEPO NINGBO KEPO ELECTRONIC CO.,LTD
<http://www.chinaacoustic.com>

Magnetic Transducer QUARTZ-1
 KP12-G185C-2933

No.	DESCRIPTION	MENDER	DATE	UNIT	SCALE
TOLERANCES UNLESS NOTED OTHERWISE				DWG/NO.	
XX ±	APPROVALS	LHJ	08.07.07	OEM2933R	
XXX ±	DRAWN			SHR	VER 1.0
90° ANGLES -1°	CHECKED				
FIRST ANGLE PROJECTION	APPROVED				